

TOWN OF LINCOLN
SPECIFICATIONS
ASPHALT PATCH
RFP 2010-22

SPECIFICATIONS:

1. Hot patch shall conform to the State of Rhode Island standard specifications for road and bridge construction specifications for Type I-I Plant Mix Bituminous Concrete Pavement.
2. Cold Patch shall be a blend of 74.5% Sand, 5.5-6.5% Bitumen, and 20% Stone passing the 5/8 Sieve and retained on the No.10 Sieve.
3. High Performance Cold Patch shall be composed of a suitable aggregate, Plant mixed with UPM liquid Asphalt blend, from the Sylvax Corporation, or equivalent. The Bituminous material shall be capable of coating various grades so that one such grade will enable a stockpile to remain pliable and workable at a temperature of -15 degrees F. The cold mix shall be capable of maintaining adhesive qualities in areas which are damp or wet at time of application, and, it shall not bleed or flush when overlaid with hot mix. Open graded mixes of this material shall be capable of maintaining all of its performance features after remaining in an uncovered stockpile of 100 tons or more, for up to twelve (12) months.
4. Delivered Hot Patch may not necessarily be all in the same area and will require moving equipment to various job sites.
5. Bid Prices shall be for the period from July 1, 2010 through June 30, 2011.

TOWN OF LINCOLN
INVITATION TO BID
ASPHALT PATCH
JUNE 2010
RFP 2010-22

NAME OF COMPANY _____

Hot Patch \$ _____ per ton

Cold Patch \$ _____ per ton

High Performance Cold Patch \$ _____ per ton

Delivery Charge \$ _____ per ton

_____ miles